

TECHNICAL INFO

The Allure Collection PENTA RIF

50x50 mm (2"x2")

SUITABILITY AREA PRODUCT & COMPOSITION GUIDE

REFERENCE	WALL	FLOOR	WET AREAS	POOLS	MATERIAL
All Products	Int/ Ext	No	Yes	No	Glass Gold

TECHNICAL CHARACTERISTICS

TEST UNE-EN-ISO 10545-3 WATER ABSORPTION	TEST UNE-EN-ISO-101-92=101 SURFACE HARDNESS. MOHS.	TEST UNE-EN-ISO 10545-9 RESISTANCE TO THERMAL SHOCKS	TEST UNE-EN-ISO 10545-12 FROST RESISTANCE	TEST UNE-EN-ISO 10545-13:1998 RESISTANCE TO CHEMICAL ATTACK			
				DOMESTIC PRODUCTS	POOL WATER ADDITIVES	LOW ACID AND ALKALINS	HIGH ACID AND ALKALINS
None	4	Resistant	Resistant	GA	-	-	-
TEST UNE-EN-ISO 10545-14 RESISTANCE TO STAINING	TEST UNE-EN-ISO 10545- 11=1997 CRACKING	DIN 51094 COLOUR STABILITY ON EXPOSURE TO LIGHT AND UV RAYS	DCOF WET DYNAMIC COEFFICIENT OF FRICTION ANSI A 137.1 STANDARD	DIN 51130:2004 SLIP RESISTANCE WEARING SHOES	DIN 51097 SLIP RESISTANCE IN BARE FEET	TEST UNE-ENV 12633:2003 (CTE) ANTI SKID COEFFICIENT, SUITABLE FOR OUTDOOR USE AND SWIMMING POOLS	
Class 5	Resistant	Resistant	-	-	-	-	

PACKING

SHEET HOJA	BOX CAJA	PALLET PALET	EURO PALLET EURO PALET
Size / Dimensión: 311x311 mm (12.24"x12.24")	Sheets / Hojas: 5	Quantity / Cantidad: 105,84 m ² (1,139.25 sqft)	Quantity / Cantidad: 70,56 m ² (759.5 sqft)
Thickness / Espesor: 5,3 mm (0.208")	Quantity / Cantidad: 0,49 m ² (5.27 sqft)	Boxes / Cajas: 216	Boxes / Cajas: 144
Weight / Peso: 1,07 Kg (2.35 lb)	Weight / Peso: 5,35 kg (11.79 lb)	Gross weight / Peso bruto: 1156kg (2,548 lb)	Gross weight / Peso bruto: 770 Kg (1,697 lb)



Minimum
Order
1 module / 1 Box



Sales
Unit
Square meters



Mosaic
Support
MESH



Gold
24K

This Artisan-edge glass mosaic is made with recycled glass pieces and may include irregular edges, rustic appearances, minimal imperfections or slight variations in sizing and squareness. These characteristics are inherent to this product due to the manufacturing process. The slight size or shape variations may affect the grout joint appearance, further enhancing the natural aspect of this product. Use constitutes acceptance.

ONIX®