Hex XL Hexagon Blends



Suitability area product & Composition guide

Wall	Floor	Wet areas	Pools	Materials
Int / Ext	No Residential ¹	Yes	Yes	Glass

¹ Hex XL Fosco Argent

Technical Characteristics

Test UNE-EN-ISO 10545-3	Test UNE-EN-ISO 101-92=101	Test UNE-EN-ISO 10545-9	Test UNE-EN-ISO 10545-12	Test UNE-EN-ISO 10545-13:1998 Resistance to chemical attack.			
Water Absorption.	Surface hardness. Mohs.	Resistance to thermal shocks.	Frost Resistance.	Domestic Products.	Pool water additives.	Low acid and alkalins.	High acid and alkalins.
None	4	Resistant	Resistant	GA	GA	GLA	GHA
Test UNE-EN-ISO 10545-14	Test UNE-EN-ISO 10545-11=1997	DIN 51094	DCOF		DIN 51130:2004 SLIP	DIN 51097 SLIP	Test UNE-ENV 12633:2003 (CTE)
Resistance to staining.	Cracking.	Colour Stability on exposure to light and UV rays.	Wet Dynamic Coefficient of Friction ANSI A 137.1 Standard.		Resistance wearing shoes.	Resistance in bare feet.	Anti skid coeffi- cient, suitable for outdoor use and swimming pools.
Class 5	Resistant	Resistant					

Packing

Sheet Hoja	5,6 mm - 0.220" Thickness	286x284 mm - 11.25"x11.18"	1 kg - 2.20 lb	
Box Caja	6 Sheets	0,49 m² - 5.27 sqft	6 kg - 13.22 lb	
Pallet Palet	180 Boxes	88,2 m² - 949.37 sqft	1087,3 kg - 2397.08 lb	
Euro Pallet Euro Palet 144 Boxes		70,56 m² - 759.50 sqft	869,8 kg - 1917.58 lb	



Made in Spain

98% Recycled Glass

Eco Friendly

Green & Sustainable Products

All ONIX 98% recycled glass mosaics series are made of molten glass. Molten glass characteristics may include irregular edges and small variations in size. These characteristics are inherent to the product and to the standard production. The small size and shape variations can affect the grout joint appearance and enhance the natural aspect of these products.











ø 51,6 mm - 2"